

ESCENE ES270-C is a professional office IP phone with rich features. It has 2.4 inch 320x240 HD color screen and up to 4 line display; it also has HD Sound Quality, unique art design, 5programmable keys and friendly user interface to satisfy users communication needs.

# **Key Features:**

- Support 2 lines;
- Support 38.5° demountable bracket;
- Support 5 programmable keys(2 Line keys, Up&Down keys, Redial key);
- Support Multi-language, e.g. Chinese, English, French, Russian, Italian and etc.
- 2\*10/100M Ethernet ports, POE is optional;
- Auto-provision, HTTP/HTTPS/TFTP/FTP;

# **ES270-C Technical Datasheet**

Security

### **Phone Features**

2 SIP accounts, MWI(Line1)

Call hold, Call waiting, Call forward, Call return; Call

transfer (blind/busy/ask)

Caller ID display, Redial, Mute, DND

Auto-answer, 3-way conferencing

Speed dial, SMS, Voicemail

Tone scheme, Volume control

Direct IP call without SIP proxy

Ring tone selection/import/delete Black list, Hand-free indicator.

Call history: dialed/received/missed;

Soft keys programmable, Supports PC control

Multi-Language:

Chinese, English, French, Russian, Italian, Polish, Portug

uesa, Portuguesa-Brasil, Spanish, Turkish

## **Advanced Features**

5 programmable keys

XML Phone Book search and input & output

Enterprise phone book(800 entries)

Personal Phonebook(300 entries)

LDAP phone book

## **IP PBX System Integration**

Busy lamp field (BLF), BLF list

Bridged line appearance (BLA)

DND & Forward synchronization

Intercom, Paging, Music on hold

Call pickup, Dial Plan, Call recording Anonymous call, Optional Feature

Anonymous call rejection

Network conference, Distinctive ring tone

Compatible with the platform













**Physical Features** 

1\* RJ9 handset port

DC 5V/1A output

Net weight: 0.62kg

**Package Features** 

Qty/CTN: 10 PCS

N.W/CTN:

G.W/CTN:

Carton Meas:

Certifications

2xRJ45 10/100M Ethernet ports

2.4inch 320x240 color screen with back light

2 LEDs: 2\* account lights, including MWI(L1)

25 keys, including 5 programmable keys,

Power adapter: AC 100~240V input and

POE ,IEEE 802.3af,class 0(Option)

Power consumption: 1.5W

Dimension: 180x157x33mm

Operating humidity: 10~95%

Storage temperature: up to 60°C

RoHS ( FC (SS)













## Transport Layer Security (TLS)

Digest authentication using MD5/MD5-sess

Secure configuration file via AES encryption

Encryption for configuration file

**Codes and Voice Features** 

VLAN QoS (802.1pq), SRTP

VAD, CNG, AEC, AGC, Full-duplex,

Wideband Codec: G.722

Phone lock for personal privacy protection

Admin/User 2-level configuration mode, LLDP, CDP

Narrowband codec: G.711µ/A, G.726, G.729AB,iLBC

L2TP VPN tunneling protocol - added

## **Network Features**

SIP v1 (RFC2543), v2 (RFC3261)

SIP connection: Proxy mode & Peering Points mode;

SRTP voice encryption(RFC3711)

Redundant server support

NAT Traversal: STUN mode

DTMF: In-Band, RFC2833, SIP Info, Auto

HTTP Web Management

IP Assignment: Static/DHCP/PPPoE

Bridge/Router mode for PC port

TFTP/DHCP/PPPoE client

Telnet/HTTP/HTTPS server, DNS client, NAT/DHCP server

## Management

Auto-provision via FTP/TFTP/HTTP/HTTPS Configuration: browser/phone/auto-provision

Trace package and system log export

TR069, IPv6, HTTPS web management, 802.1x, OPEN VPN

















## **ESCENE COMMUNICATION CO.,LTD**

Add: Floor 4 building C YueAn Industrial Park No.51 Huangcun Road Tianhe District, Guangzhou, China.

Tel: (86)20-82320720 Fax: (86)20-82326757